



Lifting Eyenut







| d | Part No. | D2 | D | d1 | Н |
|-----|----------|----|-----|----|-----|
| M6 | SKU9018 | 20 | 28 | 16 | 31 |
| M8 | SKU9020 | 20 | 36 | 20 | 36 |
| M10 | SKU9022 | 25 | 45 | 25 | 45 |
| M12 | SKU9024 | 30 | 54 | 30 | 53 |
| M16 | SKU9026 | 35 | 63 | 35 | 62 |
| M20 | SKU9028 | 40 | 72 | 40 | 71 |
| M24 | SKU9030 | 50 | 90 | 50 | 90 |
| M30 | SKU9032 | 65 | 108 | 60 | 109 |
| M36 | Ask | 75 | 126 | 70 | 128 |

Notes: Dimensions are a guide and may vary slightly. Pls check with us for dimension critical applications.

If Break (BL), Safe working load (SWL) or Working load limit (WLL) are shown:

This is a guide only. (Do not use for lifting unless it is a certified lifting product)

LIFTING EYENUT

Made from 316 stainless steel for excellent corrosion resistance. Can be used in various applications requiring tethering or holding. Not to be used for lifting. Use the Load rated eyenut for lifting applications

| MATERIAL TYPE | A4 STAINLESS |
|---------------|--------------|
| FINISH | POLISHED |