

٠A

B

## ZINC PLATED STRAIGHT LINK CHAIN

Constant of the second	
6000	
6.9	

Size (mm)	code	А	В	С
2.5	65-2.5x19-BZP	2.5	19	6.5
3	65-3x21-BZP	3	21	9
4	65-4x19-BZP	4	19	6.5
4	65-4x26-BZP	4	26	7
4	65-4x32-BZP	4	32	9
5	65-5x28-BZP	5	28	12
6	65-6x24-BZP	6	24	12
6	65-6x33-BZP	6	33	13
6	65-6x42-BZP	6	42	13

Notes : Dimensions are a guide and may vary slightly. Pls check with us for dimension critical applications. If Break (BL), Safe working load (SWL) or Working load limit (WLL) are shown: This is a guide only. (Do not use for lifting unless it is a certified lifting product)

## ZINC PLATED STRAIGHT LINK CHAIN

Straight link chain is fantastic for general and light use. It can be used for barriers, tailgates, animal ties, etc. This zinc plated chain is reasonably corrosion resistant, attractive, and exhibits a silvery bright, smooth surface. It is also refered to as Electrogalvanised chain.

MATERIAL TYPE	Steel
FINISH	Electro galavanised

- Zinc plated / electrogalvanised gives moderate corrosion resistance not to be used on the coast
- Good for use as a budget chain
- Highly durable with an attractive silvery finish

## DATASHEET

www.steelgear.co.uk info@steelgear.co.uk File name: zincplatedstraightlinkchain1.pdf